

ADAMS

"THE EFFICIENCY EXPERT"

95% EFFICIENT.....

CONDENSING OIL FIRED UNIT HEATER

50,75,100,125,000 BTU

35% MORE HEAT WITH.....

MATCHING FUEL SAVINGS



Stainless steel heat exchanger with molded pyro-ceramic combustion chamber heats up instantly on fire-up.

CTL Design Certified for U.S.A. & Canada.

Completely assembled, factory tested, unit heater for commercial applications.

Adjustable louvers put the heat where it is needed.

All models can be vertically or horizontally vented with 3" PVC pipe.

Featuring: **INTERburner** with exclusive "Turbo Reversed Air" insures smooth, positive ignition and uniform high temperature for maximum performance and whisper quiet operation.

"The Worlds Most Efficient Heater!"

PERFORMANCE RATINGS

MODEL NO.	BTU/ INPUT	BTU/ OUTPUT	EFFICIENCY	
UHEO 50	50,000	47,500	98%+	
UHEO 75	75,000	71,250	98%+	
UHEO 100	100,000	95,000	94%+	
UHEO 125	125,000	118,750	92%+	

SPECIFICATION DATA

MODEL NO.	MOTOR	BLOWER	FILTER	NOZZLE	SHIP
UHEO 50	3/4	12X12	20X25	.40 60	275
UHEO 75	3/4	12X12	20X25	.50 60	275
UHEO 100	3/4	12X12	20X25	.60 60	290
UHEO 125	3/4	12X12	20X25	.65 60	290

AIR INLET AND FLUE DIAMETER 3" ALL MODELS



U.S. & CANADIAN PATENTS PENDING

ADAMS **MANUFACTURING COMPANY**

9790 MIDWEST AVENUE CLEVELAND, OHIO 44125
(216) 587-6801 Fax (216) 587-6807 E-Mail adamsx@att.net